



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/813,420	03/20/2001	Stephen Allott	1875.8080000	2396
26111	7590	05/19/2006	EXAMINER	
STERNE, KESSLER, GOLDSTEIN & FOX PLLC 1100 NEW YORK AVENUE, N.W. WASHINGTON, DC 20005			BHATTACHARYA, SAM	
			ART UNIT	PAPER NUMBER
			2617	

DATE MAILED: 05/19/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

<b>Office Action Summary</b>	<b>Application No.</b> 09/813,420	<b>Applicant(s)</b> ALLOTT ET AL.	
	<b>Examiner</b> Sam Bhattacharya	<b>Art Unit</b> 2617	

**-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --**

**Period for Reply**

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☒ Responsive to communication(s) filed on 24 February 2006.
- 2a) ☐ This action is **FINAL**.                      2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 4) ☒ Claim(s) 2-10 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☒ Claim(s) 7 is/are allowed.
- 6) ☒ Claim(s) 2-6 8-10 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
     Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
     Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All    b) ☐ Some \*    c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- \* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- |  |   |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892)  | 4) <input type="checkbox"/> Interview Summary (PTO-413)<br>Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)                                   | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152)             |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)<br>Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____  |

**DETAILED ACTION**


1. In view of the Appeal Brief filed on 2/24/06, PROSECUTION IS HEREBY REOPENED. A new ground of rejection is set forth below.

To avoid abandonment of the application, appellant must exercise one of the following two options:

(1) file a reply under 37 CFR 1.111 (if this Office action is non-final) or a reply under 37 CFR 1.113 (if this Office action is final); or,

(2) initiate a new appeal by filing a notice of appeal under 37 CFR 41.31 followed by an appeal brief under 37 CFR 41.37. The previously paid notice of appeal fee and appeal brief fee can be applied to the new appeal. If, however, the appeal fees set forth in 37 CFR 41.20 have been increased since they were previously paid, then appellant must pay the difference between the increased fees and the amount previously paid.

A Supervisory Patent Examiner (SPE) has approved of reopening prosecution by signing below:

  
GEORGE ENG  
SUPERVISORY PATENT EXAMINER

***Claim Rejections - 35 USC § 103***

2. The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.

3. Claims 2-4 are rejected under 35 U.S.C. 103(a) as being unpatentable over Luz et al. (US 6,321,073) in view of Nielsen (US 6,985,518).

As to claim 2, Figures 1 and 2 in Luz show a radio receiver (100) (see Col. 2, lines 40-67), comprising:

an amplifier (104a, 104b, 104c) configured to receive and amplify an intermediate frequency modulated signal having in-phase and quadrature phase DC components;

an analog-to-digital converter (110) configured to receive the amplified intermediate frequency modulated signal and convert it to a digital signal;

a demodulator (202) operable to demodulate the digital signal; and

DC offset calibration means (202) coupled to the demodulator operable to provide in-phase and quadrature phase DC offset correction signals to compensate for the in-phase and quadrature phase DC components at the input of the amplifier (“the feedforward DC offset compensation circuit 202 generates an in-phase digital error signal 360a (see FIG. 3A) and a quadrature phase DC error signal 360b to remove DC offsets introduced by the ADC or other sources. These signals are combined and subtracted from the signal” (Col. 3, lines 10-14)).

Luz fails to disclose delay measurement means coupled to the demodulator operable to determine a delay vector.

However, in an analogous art, Nielsen discloses a receiver including delay measurement means 32 coupled to the demodulator 36 operable to determine delay vectors. See FIG. 2 and col. 4, lines 7-45. Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the receiver in Luz by incorporating the above-noted features taught in Nielsen for the purpose of determining correction values to compensate for directional components of the offset signal.

As to claim 3, the Luz reference discloses the radio receiver of claim 2, wherein the delay vector is used by the DC offset calibration means to provide a digital representation of the in-phase and quadrature phase DC offset correction signals (“Each of these results is truncated into

a 20-bit results in truncators 358a and 358b. The result is a DC offset error 360a for the in-phase signal and a DC offset error 360b for the quadrature phase signal” (Col. 4, lines 35-38). See also Col. 4, lines 20-35).

As to claim 4, Luz (Figure 3b) discloses the radio receiver of claim 3, further comprising: a first digital-to-analog converter (386) configured to receive a in-phase component of the digital representation of the in phase DC offset correction signal for mixing with an in-phase signal and an intermediate frequency carrier signal; a second digital-to-analog converter (388) configured to receive a quadrature phase component of the digital representation of the quadrature phase DC offset correction signal for mixing with a quadrature signal and the intermediate frequency carrier signal (“the gain control 384 is input to digital analog converters 386 and 388 simultaneously so that gain control is applied to all gain stages at the same time” (Col. 5, lines 1-3)); and

a summer operable to subtract the mixed quadrature phase signal and quadrature phase DC offset correction signal component from the mixed-in phase signal and in-phase DC offset correction signal to provide a DC compensated intermediate frequency modulated signal at the input of the low noise amplifier (“these DC offset errors 360a and 360b are combined in an error combiner 362 and a net offset error 364 is subtracted in subtractor 332 with the signal 330 to obtain a DC compensated input signal 366” (Col. 4, lines 38-41)).

4. Claims 5-6 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent 6,321,073 to Luz et al. in view of Nielsen (US 6,985,518) and Galal et al. (U.S. Patent 6,161,004).

As to claim 5, the Luz reference (Figures 1 and 2) discloses a radio receiver (100) (see Col. 2, lines 40-67), comprising:

an automatic gain control stage (104a, 104b, 104n) coupled to the summer and operable to amplify the integrated signal;

an analog-to-digital converter (110) operable to convert the amplified integrated signal to a digital signal;

a demodulator (202) operable to demodulate the digital signal; and

Luz fails to disclose delay measurement means coupled to the demodulator operable to determine a delay vector.

However, in an analogous art, Nielsen discloses a receiver including delay measurement means 32 coupled to the demodulator 36 operable to determine delay vectors. See FIG. 2 and col. 4, lines 7-45. Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the receiver in Luz by incorporating the above-noted features taught in Nielsen for the purpose of determining correction values to compensate for directional components of the offset signal.

The combination of Luz and Nielsen does not disclose a receiving stage configured to receive a radio signal; a first mixer stage operable to downconvert the radio frequency signal to a first intermediate frequency in-phase signal and a first intermediate quadrature phase signal; first and second low pass filters configured to receive and low pass filter the first intermediate frequency in-phase and quadrature phase signals; a second mixer stage operable to upconvert the filtered first intermediate frequency in-phase and quadrature phase signals and provide a second intermediate frequency in-phase signal and a second intermediate frequency quadrature phase

Art Unit: 2617

signal; and a summer operable to subtract the second intermediate frequency quadrature phase signal from the second intermediate frequency in-phase signal to provide an integrated signal;

The Galal reference teaches a receiving stage configured to receive a radio signal; a first mixer stage operable to downconvert the radio frequency signal to a first intermediate frequency in-phase signal and a first intermediate quadrature phase signal; first and second low pass filters configured to receive and low pass filter the first intermediate frequency in-phase and quadrature phase signals; a second mixer stage operable to upconvert the filtered first intermediate frequency in-phase and quadrature phase signals and provide a second intermediate frequency in-phase signal and a second intermediate frequency quadrature phase signal; and a summer operable to subtract the second intermediate frequency quadrature phase signal from the second intermediate frequency in-phase signal to provide an integrated signal (see Figure 18 and Col. 10, line 8 to Col. 11, line 56).

Therefore, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the device of Luz and Nielsen to comprise a receiving stage configured to receive a radio signal; a first mixer stage operable to downconvert the radio frequency signal to a first intermediate frequency in-phase signal and a first intermediate quadrature phase signal; first and second low pass filters configured to receive and low pass filter the first intermediate frequency in-phase and quadrature phase signals; a second mixer stage operable to upconvert the filtered first intermediate frequency in-phase and quadrature phase signals and provide a second intermediate frequency in-phase signal and a second intermediate frequency quadrature phase signal; and a summer operable to subtract the second intermediate frequency quadrature phase signal from the second intermediate frequency in-phase signal to

provide an integrated signal, as taught by Galal, in order to implement a dual path mixing network to provide for balanced gain and group delay distortion among the upper and lower paths of the mixing network.

As to claim 6, Luz-Galal discloses the radio receiver of claim 5. The Luz reference further teaches: a DC offset calibrator coupled to the delay measurement means (see Col. 4, lines 20-38); an in-phase digital-to-analog converter coupled between the DC offset calibrator and the second mixer stage; and a quadrature phase digital-to-analog converter coupled between the DC offset calibrator and the second mixer stage, wherein the in-phase digital-to-analog converter is operable to provide an in-phase DC offset compensation signal for the automatic gain control stage and the quadrature phase digital-to-analog converter is operable to provide a quadrature phase DC offset compensation signal for the automatic gain control stage (“the gain control 384 is input to digital analog converters 386 and 388 simultaneously so that gain control is applied to all gain stages at the same time” (Col. 5, lines 1-3). See also Col. 4, lines 38-67).

5. Claims 8 and 10 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent Application Publication 2002/0114413 A1 to Zarubinsky et al. in view of Nielsen and Galal et al. (U.S. Patent 6,161,004).

As to claim 8, the Zarubinsky reference discloses a method of compensating for DC offset voltages present at an input of a low noise amplifier, the method comprising the steps of:

determining a signal delay between an output of a second mixer stage of the dual mixer stage radio receiver, said signal delay characterizing in phase and quadrature phase components of the DC offset voltage present at the input of the low noise amplifier (“delay stage 207



Art Unit: 2617

forwards signal  $X'_D$  with a delay of  $N$  time slots  $T$ . The symbol  $Z_{-N}$  is an operator of a  $Z$ -transformation. Persons of skill in the art can implement delay stage 207 without the need of detailed explanation herein, for example, by a shift register. The delay of stage 207 conveniently corresponds to the intrinsic input-to-output delay introduced in in-phase channel 291 (e.g., by DAC 293, LPF 295. This is convenient. As explained in connection with FIG. 3, the “input related” signal  $X_D$  is combined with the delayed “output related”  $X_A$  (page 5, col. 1, paragraph [0077]));

using the determined signal delay to separate and define digital representations of the in-phase DC offset voltage component and the quadrature phase DC offset voltage component (“FIG. 9 illustrates a simplified block diagram of offset compensation control loop 401” (page 5, col. 2, paragraph [0094], lines 1-2). “Integrator 441 obtains an estimation of the magnitude and feeds back a compensation offset signal  $OCOMP(P,P)$  to either one of the inputs of corresponding digital comparator 221. In the example of FIG. 9, this implemented by subtracting  $OCOMP(P,P)$  from  $ID(P)$  by subtractor 411. Delay stage 431 delays by the delay time introduced by channel 292” (page 5, col. 2, paragraph [0095]));

making the digital representation of each of the in-phase and quadrature phase components more positive or more negative if it is more negative or more positive than a predetermined minimum threshold or maximum threshold; and performing the above sequence of steps a predetermined number of times to reduce the DC offset voltage at the input of the low noise amplifier (see page 6, col. 1, paragraphs [0097] and [0098]).

Zarubinsky fails to disclose that the determination of the delay has component delay vectors. However, in an analogous art, Nielsen discloses a receiver including delay measurement

Art Unit: 2617

means 32 coupled to the demodulator 36 operable to determine delay vectors. See FIG. 2 and col. 4, lines 7-45. Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the receiver in Luz by incorporating the above-noted features taught in Nielsen for the purpose of determining correction values to compensate for directional components of the offset signal.

However, the combination of Zarubinsky and Nielsen does not expressly disclose a dual mixer stage radio receiver. The Galal reference teaches a dual mixer stage radio receiver (Figure 18 and Col. 10, line 8 to Col. 11, line 56).

Therefore, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the method of Zarubinsky and Nielsen for a dual mixer stage radio receiver, as taught by Galal, in order to implement a dual path mixing network to provide for balanced gain and group delay distortion among the upper and lower paths of the mixing network.

As to claim 10, the Zarubinsky reference discloses a method of compensating for DC offset voltages at inputs of in-phase and quadrature phase low pass filters, said method comprising the steps of:

determining a signal delay between the inputs of the low pass filters, said signal delay characterizing in-phase and quadrature phase components of DC offset voltages at the inputs of the low pass filters ("delay stage 207 forwards signal  $X'_D$  with a delay of  $N$  time slots  $T$ . The symbol  $Z_{-N}$  is an operator of a  $Z$ -transformation. Persons of skill in the art can implement delay stage 207 with out the need of detailed explanation herein, for example, by a shift register. The delay of stage 207 conveniently corresponds to the intrinsic input-to-output delay introduced in

in-phase channel 291 (e.g., by DAC 293, LPF 295. This is convenient. As explained in connection with FIG. 3, the “input related” signal  $X_D$  is combined with the delayed “output related”  $X_A$  (page 5, col. 1, paragraph [0077]));

using the signal delay to separate and define in-phase and quadrature phase multiplication factors associated with the in-phase and quadrature phase DC offsets (“FIG. 9 illustrates a simplified block diagram of offset compensation control loop 401” (page 5, col. 2, paragraph [0094], lines 1-2). “Integrator 441 obtains an estimation of the magnitude and feeds back a compensation offset signal OCOMP (P,P) to either one of the inputs of corresponding digital comparator 221. In the example of FIG. 9, this implemented by subtracting OCOMP (P,P) from ID(P) by subtractor 411. Delay stage 431 delays by the delay time introduced by channel 292” (page 5, col. 2, paragraph [0095]));

incrementally adjusting the signal level of the in-phase component to a more positive or more negative value if the in-phase multiplication factor has a negative or positive value, respectively; and incrementally adjusting the signal value of the quadrature phase component to a more positive or more negative value if the quadrature phase multiplication factor has a negative or positive value, respectively (see page 6, col. 1, paragraphs [0097] and [0098]).

Zarubinsky fails to disclose that the determination of the delay has component delay vectors. However, in an analogous art, Nielsen discloses a receiver including delay measurement means 32 coupled to the demodulator 36 operable to determine delay vectors. See FIG. 2 and col. 4, lines 7-45. Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the receiver in Luz by incorporating the above-noted

Art Unit: 2617

features taught in Nielsen for the purpose of determining correction values to compensate for directional components of the offset signal.

However, the combination of Zarubinsky and Nielsen does not expressly disclose a dual mixer stage radio receiver. The Galal reference teaches a dual mixer stage radio receiver (Figure 18 and Col. 10, line 8 to Col. 11, line 56).

Therefore, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the method of Zarubinsky and Nielsen for a dual mixer stage radio receiver, as taught by Galal, in order to implement a dual path mixing network to provide for balanced gain and group delay distortion among the upper and lower paths of the mixing network.

6. Claim 9 is rejected under 35 U.S.C. 103(a) as being anticipated by Zarubinsky et al. (U.S. Patent Application Publication 2002/0114413 A1) in view of Ma et al. (US 4,816,769).

As to claim 9, the Zarubinsky reference discloses a method of setting signal levels of in-phase and quadrature phase components of a radio receiver between a minimum threshold voltage and a maximum threshold voltage, the method including setting the gain of an automatic gain control, increasing the gain of the automatic gain control stage by a predetermined amount and repeating these steps until the signal levels of the in-phase and quadrature phase components are greater than or equal to the predetermined minimum threshold value (see page 2, col. 1, paragraphs [0028], [0030], [0031]; and page 5, col. 2, paragraphs [0089] to [0092]).

Zarubinsky fails to disclose setting the gain to a value at which the signal levels of the in phase and quadrature phase components are less than or equal to the maximum threshold

voltage, and comparing the signal levels of the in-phase and quadrature phase components to a predetermined minimum threshold value.

However, in an analogous art, Ma discloses a receiver in which a gain to a value at which the signal levels of the in phase and quadrature phase components are less than or equal to the maximum threshold voltage, and comparing the signal levels of the in-phase and quadrature phase components to a predetermined minimum threshold value. See col. 7, lines 23-42. Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the method in Zarubinsky by including the above-noted features taught in Ma for the purpose of fine tuning the levels of the in phase and quadrature phase components to desired values.

*Allowable Subject Matter*

7. Claim 7 is allowed.
8. The following is a statement of reasons for the indication of allowable subject matter: the prior art fails to disclose the recited combination of elements in a method of determining a signal delay between inputs of first and second low pass filters, including storing the first in-phase and quadrature phase components if the value of each component is less than the predetermined maximum threshold value; applying the negative of the first known voltage to the input of the in-phase mixer; applying the value of the second known voltage to the input of the quadrature phase mixer; measuring second in-phase and second quadrature phase components at the output of the demodulator; decreasing the gain of the automatic gain control stage by a predetermined amount if the value of each second component is greater than the predetermined maximum threshold

Art Unit: 2617

value; storing the second in-phase and quadrature phase components if the value of each second component is less than the predetermined maximum threshold value; and using the first and second quadrature phase components to compute the signal delay, as set forth in claim 7.

### ***Response to Arguments***

9. Applicant's arguments with respect to the claims have been considered but are moot in view of the new ground(s) of rejection.

### ***Conclusion***


Any inquiry concerning this communication or earlier communications from the examiner should be directed to Sam Bhattacharya whose telephone number is (571) 272-7917. The examiner can normally be reached on Weekdays, 9-6, with first Fridays off.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, George Eng can be reached on (571) 272-7495. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2617

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

sb

  
GEORGE ENG  
SUPERVISORY PATENT EXAMINER